

**BRASS HOSE  
FERRULES**



PART NO.	INSIDE DIAMETER	LENGTH	RECOMMENDED HAND CRIMP TOOL	5111-A DIE	
				PLAIN	RIBBED
<b>Listed By Size In Inches * Smallest To Largest ID</b>					
6231	.330	1/2"	C-5A	-	CDR-46
833	.358	1/2"	C-5A	-	CDR-45
622	.380	1/2"	C-5A	-	-
620	.410	1/2"	C-5A	-	-
769	.450	9/16"	C-1, C-5, C-5A, CR-100	-	CDR-41
4750	.478	11/16"	CR-100	-	CDR-41
624	.500	1/2"	CR-100	-	CDR-40
7322	.500	1"	C-3B	-	CDR-39
625	.525	1/2"	C-3B	-	CDR-39
7323	.525	1"	C-3B	CD-38	CDR-38
626	.548	31/64"	C-3B	-	CDR-38
7325	.562	1"	C-3B, C-5, CR-100	CD-38	CDR-37
3588	.564	3/4"	C-3B, C-5, CR-100	CD-38	CDR-37
K-K	.575	31/64"	C-1, C-3B, C-5, C-3, CR-100	CD-38	CDR-37
7326	.593	1"	C-1, C-3B, C-3, C-5	-	CDR-36
J-J	.600	1/2"	C-1, C-3B, C-3, C-5	-	CDR-36
I-I	.625	1/2"	C-3B, C-6, CR-100	-	CDR-35
7327	.625	1"	C-3B, C-6, CR-100	-	CDR-35
H-H	.650	1/2"	C-6	-	CDR-34
7328	.656	1"	C-3B, C-6, CR-100	-	CDR-34
G-G	.675	33/64"	C-3B, C-6, CR-100	-	-
7329	.687	1"	C-3, C-6, CR-100	-	-
F-F	.700	33/64"	C-3, C-6, CR-100	-	CDR-32
7330-B	.718	1"	C-3, C-6	-	-
E-E	.725	17/32"	C-3, C-6	-	-
7331	.750	1"	C-3, C-6	-	-
C-C	.775	17/32"	C-3, C-6	-	-
7332	.781	1"	C-3, C-6	-	-
7333	.812	1"	5111-A**	CD-28	-
7244-A	.875	27/32"	5111-A**	CD-26	CDR-25
5029-A	.900	27/32"	5111-A**	CD-25	-
7242-A	.937	27/32"	5111-A**	-	-
5028-A	.975	27/32"	5111-A**	CD-22	-

Since there is no industry standard for hose wall thickness, the ID of the hose cannot be used to determine the correct ferrule. To determine the proper size ferrule, measure the OD of the hose (as a decimal) and go up to the next larger size Ferrule ID listed above.

**Example: If the hose OD is .555 "use a #7325 Ferrule, which has an ID of .562".**

See page 19 for listing and descriptions of all Western hand crimp tools and model 5111-A bench tool.

\*\* Use of hand tool is not recommended. Model 5111-A is a heavy-duty bench style ferrule machine.